



ICS Performance Guarantee Durability Chart

- UV Printed Digital Inkjet Printer Graphics (chart 1)

[Reference Avery Dennison Graphics ICS Performance Guarantee \(Terms & Conditions\) for details](#)

Expected Durability in Years, vertical exposure zone 1¹

Reference Product Data sheet for recommended applications

		Durst Rho				EFI				HP				Canon				Ricoh				Roland			
		160, 160 plus, 160R, 320R, 351R, 500R and 205 UV				GS3250, 3200R, 5000R, 3250LX Pro				FB6100, H35100, H35500, H45500, FP910				Colorado 1650, 1630				Pro TF6251 UV				LEC2-640			
		Durst UV				GS Premium, GSr Premium, GSLXr SuperFlex				FB200, SolaChrome0UV				UVgel 460				GP120				EUV5			
MPI	DOL	Outdoor	Vehicles	Marine	Indoor	Outdoor	Vehicles	Marine	Indoor	Outdoor	Vehicles	Marine	Indoor	Outdoor	Vehicles	Marine	Indoor	Outdoor	Vehicles	Marine	Indoor	Outdoor	Vehicles	Marine	Indoor
1105, 1106HTEZ, 1060	1000Z Series	5	5	3	8	5	5	3	8	5	5	3	8	5	5	3	8	4	4	2	7	5	5	3	8
	1300Z, 1460Z Series	4	4	3	7	4	4	3	7	4	4	3	7	4	4	3	7	4	4	2	7	4	4	3	7
	6040	2	2	2	2	2	2	2	2	2	2	2	2	2	2	2	2	2	2	2	2	2	2	2	2
	6460*	5/3	5/3	3	8	5/3	5/3	3	8	5/3	5/3	3	8	5/3	5/3	3	8	3	3	1	6	2	2	1	5
1405	6460*	5/3	--	3	8	5/3	--	3	8	5/3	--	3	8	5/3	--	3	8	3	--	1	6	2	--	--	5
2050, 2105 EZ, 2105 EZRS, 2120, 2126 HTEZ, 2900, 2902, 2903, 2903 EZ, 2929, 2922, 2923, 2923 EZ	1000Z Series	5	5	--	5	5	5	--	5	5	5	--	5	5	5	--	5	4	4	2	4	5	5	2	5
	1300Z, 1460Z Series	4	4	--	4	4	4	--	4	4	4	--	4	4	4	--	4	4	4	2	4	4	4	2	4
	2000 Series	3	3	--	3	3	3	--	3	3	3	--	3	3	3	--	3	3	3	--	3	3	3	--	3
	3000 Series, 6040	2	2	--	2	2	2	--	2	2	2	--	2	2	2	--	2	2	2	--	2	2	2	--	2
3300, 3320, 3303, 3323, 3302, 3322	1000Z, 1300Z, 1400Z, 2000 Series	3	3	--	3	3	3	--	3	3	3	--	3	3	3	--	3	3	3	--	3	3	3	--	3
	3000 Series, 6040	2	2	--	2	2	2	--	2	2	2	--	2	2	2	--	2	2	2	--	2	2	2	--	2
2610, 2611 Wall Film	1000Z, 1300Z, 1400Z, 2000 Series	3	3	--	3	3	3	--	3	3	3	--	3	3	3	--	3	3	3	--	3	3	3	--	3
	3000 Series, 6040	2	2	--	2	2	2	--	2	2	2	--	2	2	2	--	2	2	2	--	2	2	2	--	2
2630 & 2631 Wall Film	Unprotected	--	--	--	2	--	--	--	2	--	--	--	2	--	--	--	2	--	--	--	2	--	--	--	2
2121 Transit Vinyl, 2921, 2921 EZ	1000Z, 1300Z, 1400Z, 2000, 3000 Series, 6040	1	1	--	1	1	1	--	1	1	1	--	1	1	1	--	1	1	1	--	1	1	1	--	1



ICS Performance Guarantee Durability Chart

- UV Printed Digital Inkjet Printer Graphics (chart 1)

[Reference Avery Dennison Graphics ICS Performance Guarantee \(Terms & Conditions\) for details](#)

Expected Durability in Years, vertical exposure zone 1¹

Reference Product Data sheet for recommended applications

MPI	DOL	Durst Rho				EFI				HP				Canon				Ricoh				Roland			
		Outdoor	Vehicles	Marine	Indoor	Outdoor	Vehicles	Marine	Indoor	Outdoor	Vehicles	Marine	Indoor	Outdoor	Vehicles	Marine	Indoor	Outdoor	Vehicles	Marine	Indoor	Outdoor	Vehicles	Marine	Indoor
<u>2077</u>	<u>1000Z, 1300Z, 1400Z, 2000, 3000 Series, 6040</u>	1	-	-	1	1	-	-	1	1	-	-	1	1	-	-	1	1	-	-	1	1	-	-	1
<u>2528 (50/50)</u> <u>2728 (65/35)</u>	<u>1360 Optically Clear</u>	1	1	-	2	1	1	-	2	1	1	-	2	1	1	-	2	1	1	-	2	1	1	-	2
<u>V8000, V4000</u>	<u>1000Z Series</u>	5	5	3	8	5	5	3	8	5	5	3	8	5	5	3	8	4	4	2	6	5	5	1	8
	<u>1300Z, 1460Z Series</u>	4	4	3	7	4	4	3	7	4	4	3	7	4	4	3	7	4	4	2	6	4	4	2	6
<u>SF100-103 Ultra Clear</u>	Unprotected	2	--	--	2	2	--	--	2	2	--	--	2	2	--	--	2	2	--	--	2	2	--	--	2

*DOL6460 when there are two numbers separated by a slash the first number designates vertical durability and the second number designates horizontal durability.

¹Zone 1 vertical exposure: Instructional Bulletin # 1.30 for durability guidelines. Unless otherwise stated, horizontal applications do not have any expectations of durability and Avery Dennison shall have no liability with respect to such installations. The exposure of films in the horizontal position voids any performance expectations as outlined in appropriate Product Data Bulletins and Instructional Bulletins. Films may retain legibility, but will not provide published Expected Durability for gloss, color retention, chalking, and overall aesthetic performance.

NOTES:

- If the stated durability of an approved allied component (ink, qualified clear coat) differs from that of the Avery Dennison material the finished graphics will be warranted for a period equal to the stated durability of the least durable component.
- This is an expected durability only. The printer maintains the ultimate responsibility for proper processing, ink drying, and print quality
- Unless otherwise stated, there is no expectation of durability for white, metallic, orange and green inks.
- Reference Instructional Bulletins 4.07 and 6.40 for information regarding UV ink conformability and post heating.
- With many UV inks there is the possibility of fine entrapment of air at the micro level, also known as "silvering" during the application of protective laminate. Changes to the heat, pressure, or speed of the maintain process may address silvering, but the presence of silvering is not covered by the ICS PG
- **Durst Rho, HP, Ricoh and Roland UV inks are recommended for flat and simple curves only. Not for use on rivets, compound curves or corrugations.**
- **Canon UVgel inks are recommended for vehicle graphics including flat, simple curves, trailers with rivets or rivets & corrugations only. Not for use on wraps which have compound curves, mirrors wrapped, or other highly stretched and conformable applications.**