



DS Print SR 4 Mil - DS Print SR Interior Films

Clear printable UV films for custom window graphics



DS Print SR - 4 Mil interior window film is engineered for UV wide format inkjet printers. This optically clear PET-based film with scratch resistant coating with ultraviolet block, delivers vivid graphics suitable for large scale branding and decorative interior design.

Optical and Solar Properties**	DS Print SR 4 mil
Item Number	R12325SR
Pane	Single
Visible Light Transmitted	89%
Visible Light Reflected (Interior)	11%
Visible Light Reflected (Exterior)	11%
Ultra Violet Block	90%
Total Solar Energy Reflected	10%
Total Solar Energy Transmitted	81%
Total Solar Energy Absorbed	9%
Emissivity (Room Side)	0.82
Glare Reduction	1%
Shading Coefficient	0.97
Solar Heat Gain Coeff. (G-Value)	0.84
U-Value Winter (IP)	1.03
U-Value Winter (SI)	5.85
Luminous Efficacy	0.92
Total Solar Energy Rejected (%)	16%

** Performance results are calculated on 3 mm glass using NFRC methodology and LBNL Window 5.2 software, and are subject to variations in process conditions within industry standards and are only intended for estimating purposes.

S93017 4/19



Graphics Solutions

Avery Dennison Graphics Solutions
 Norton Parkway 8080
 Mentor, Ohio 44060
 T: 1-800-660-5559
[windowfilm.orders@averydennison.com](mailto>windowfilm.orders@averydennison.com)